

View Online at <https://aerobasegroup.com/nsn/5320-00-455-0545>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.248 inches and 1.268 inches

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.095 inches and 0.097 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Grip Length:

0.943 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

50.0 rockwell c and 55.0 rockwell c

Thread Size:

0.250 inches

Shear Strength:

156000 single pounds per square inch

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium or nickel and cadmium

Surface Treatment Specification:

Mil-c-8837, type 2, cl 2 military specification 1st treatment response or ams 2416 assn standard 2nd treatment response or ams 2416 assn standard 3rd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.