
# NSN 5320-00-462-3473

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.940 inches and 0.960 inches

### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

### Width Between Flats:

Between 0.079 inches and 0.081 inches

### Shank Diameter:

Between 0.189 inches and 0.190 inches

#### Shank Style:

### Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Cetyl alcohol

# Grip Length:

0.630 inches

## Thready Qty Per Inch (tpi):

32

### Thread Size:

0.190 inches

### Shear Strength:

95000 single pounds per square inch

### Material:

Titanium alloy

### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Cadmium

### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--



# NSN 5320-00-462-3473

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

