## NSN 5320-00-464-8666

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-464-8666



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.115 inches and 1.135 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

#### Width Between Flats:

Between 0.127 inches and 0.130 inches

#### Shank Diameter:

Between 0.311 inches and 0.312 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

#### Lubrication:

Cetyl alcohol

#### Grip Length:

0.630 inches

## Thread Size:

0.312 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp 431

#### **Material Specification:**

Mil-s-18732 military specification single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-00-464-8666

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

