NSN 5320-00-464-8679

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-464-8679 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.565 inches and 1.585 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.202 inches and 0.203 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Grip Length:** 1.255 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches Material: Steel comp 4140 or steel comp 8740 or steel comp 4130 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-00-464-8679

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.