## NSN 5320-00-466-0516

Blind Rivet - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/5320-00-466-0516   |
|---|
| Fastener Length:  |
| Between 1.329 inches and 1.359 inches   |
| Head Style:   |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)  |
| Shank Diameter:   |
| Between 0.258 inches and 0.260 inches   |
| Shank Style:  |
| Self-plugging mechanically locked stem  |
| Head Major Diameter:  |
| 0.507 inches  |
| Expansion Device:   |
| Serrated stem-type w  |
| Grip Length:  |
| Between 1.094 inches and 1.157 inches   |
| Hardness Rating:  |
| 48.0 rockwell c stem and 53.0 rockwell c stem   |
| Shear Strength:   |
| 5900 single pounds per square inch  |
| Countersink Angle:  |
| Between 99.0 degrees and 101.0 degrees  |
| Material:   |
| Steel comp 8740 stem or steel comp 8740 stem  |
| Material Specification:   |
| Qq-w-405 federal specification 1st material response stem or mil-s-6049 military specification 2nd material response stem |
| Surface Treatment:  |
| Cadmium stem  |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, cl 2 federal specification single treatment response body   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A040a0  |
| Mil-std (military Standard):  |

Mil-s-6758 spec.