

View Online at <https://aerobasegroup.com/nsn/5320-00-467-0509>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.040 inches and 1.090 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.125 inches and 0.127 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.350 inches and 0.399 inches

Grip Length:

Between 0.678 inches and 0.698 inches

Min. Tensile Strength (psi):

260000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

156000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp h11 or steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard 1st material response

Surface Treatment:

Nickel and zinc

Surface Treatment Specification:

Ams 2417 assn standard all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas1294 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0