# NSN 5320-00-468-1241

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-468-1241

## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.127 inches and 1.147 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.079 inches and 0.081 inches

#### Shank Diameter:

Between 0.189 inches and 0.190 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### End Application:

W/s: aircraft, hercules c-130; aircraft, prowler ea-6b; aircraft, starlifter c-141; aircraft, galaxy c-5

### Grip Length:

Between 0.812 inches and 0.822 inches

### **Thread Size:**

0.190 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp 431

#### **Material Specification:**

Mil-s-18732 military specification single material response

#### Surface Treatment:

Cadmium and chromate

### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5320-00-468-1241

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

