## NSN 5320-00-468-3041

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-468-3041 **Head Style:** Err-090 **Head Height:** Between 0.099 inches and 0.111 inches Shank Diameter: Between 0.1880 inches and 0.1895 inches **Shank Style:** Pin-rivet, multiple grooved **Head Major Diameter:** Between 0.297 inches and 0.327 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.407 inches and 0.469 inches **Features Provided:** Casehardened and sealant vent groove Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 77.2 rockwell superficial 15-n and 82.0 rockwell superficial 15-n **Shear Strength:** 95000 single pounds per square inch Material: Steel comp 8740 or steel comp 4340 or steel comp 4140 **Material Specification:** Astm a547 assn standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Specification Data:** 80205-nas1466 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A528u0