NSN 5320-00-470-3619

Solid Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-a-8625 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-470-3619

| Fastener Length: |
|--|
| Between 0.678 inches and 0.698 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.186 inches and 0.190 inches |
| Shank Style: |
| Straight w/radius chamfered tip |
| Head Major Diameter: |
| Between 0.349 inches and 0.357 inches |
| Shear Strength: |
| 26000 single pounds per square inch |
| Countersink Angle: |
| Between 99.5 degrees and 100.5 degrees |
| Heat Treatment: |
| T-4 solution heat treated |
| Material: |
| Aluminum alloy 2117 |
| Material Specification: |
| Qq-a-430 federal specification single material response |
| Surface Treatment: |
| Anodize or oxide film |
| Surface Treatment Specification: |
| Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |