## NSN 5320-00-470-8229

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-470-8229



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.690 inches and 0.710 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.079 inches and 0.081 inches

#### Shank Diameter:

Between 0.189 inches and 0.190 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### Grip Length:

0.380 inches

#### Thread Size:

0.190 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp h11

#### **Material Specification:**

Ams 6485 assn standard single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Mil-c-8837, type 2, cl 3 military specification single treatment response

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A528u0

# NSN 5320-00-470-8229

Pin-rivet - Page 2 of 2

### Mil-std (military Standard):

Mil-c-8837 spec.

