## NSN 5320-00-476-0035

Demilitarization:

No Fiig: A040a0



Tubular Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-476-0035 **Fastener Length:** Between 0.565 inches and 0.575 inches **Head Style:** Flat fillister **Head Height:** Between 0.060 inches and 0.065 inches **Hole Diameter:** 0.125 inches **Shank Diameter:** Between 0.26775 inches and 0.26875 inches **Shank Style:** Tubular **Head Major Diameter:** Between 0.340 inches and 0.350 inches **Hole Depth:** 0.530 inches **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Criticality Code Justification:** Aaze Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Ams 2481 assn standard single treatment response **Test Data Document:** 81343-ams2640 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure:**