## NSN 5320-00-476-7390

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-476-7390

## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.770 inches and 0.795 inches

#### Head Style:

Flush countersunk

#### Shank Diameter:

0.2001 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

0.413 inches

#### Tip Diameter:

## 0.1925 inches

Lubrication:

Cetyl alcohol

#### Grip Length:

Between 0.490 inches and 0.505 inches

## Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.190 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Titanium alloy

#### Material Specification:

Ams 4928 assn standard single material response

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas1724 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No



# NSN 5320-00-476-7390

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

