NSN 5320-00-490-2235

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-490-2235

Fastener Length:
Between 0.642 inches and 0.676 inches
Head Style:
Oval/truss
Head Height:
Between 0.062 inches and 0.082 inches
Shank Diameter:
Between 0.186 inches and 0.190 inches
Shank Style:
Self-plugging
Head Major Diameter:
Between 0.600 inches and 0.650 inches
Expansion Device:
Plain stem-type t
Grip Length:
Between 0.376 inches and 0.500 inches
Shear Strength:
425 single pounds per square inch
Material:
Aluminum alloy 5056 stem
Material Specification:
Qq-a-430 federal specification single material response stem
Surface Treatment:
Cadmium stem or cadmium stem and chromate stem or cadmium stem and phosphate stem or phosphate zinc stem or phosphate zinc stem
or zinc stem and chromate stem
Surface Treatment Specification:
Qq-p-416 federal specification 1st treatment response stem or mil-16232, ty z, cl 2 military specification 2nd treatment response stem or
mil-z-16232, ty z, cl 4b military specification 4th treatment response stem
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-a-8625 spec.