

View Online at <https://aerobasegroup.com/nsn/5320-00-490-2241>

Fastener Length:

Between 0.517 inches and 0.547 inches

Head Style:

Oval/truss

Head Height:

Between 0.062 inches and 0.082 inches

Shank Diameter:

Between 0.186 inches and 0.190 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.600 inches and 0.650 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.250 inches and 0.375 inches

Shear Strength:

425 single pounds per square inch

Material:

Aluminum alloy 5056

Material Specification:

Qq-a-430 federal specification single material response

Surface Treatment:

Cadmium mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or phosphate zinc mandrel or zinc mandrel and chromate mandrel

Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses mandrel or mil-p-16232 military specification 1st treatment response mandrel or qq-z-325, type 2, cl 3 federal specification 2nd treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.