## NSN 5320-00-490-2241

Blind Rivet - Page 1 of 1

A040a0

Mil-a-8625 spec.

Mil-std (military Standard):



View Online at https://aerobasegroup.com/nsn/5320-00-490-2241 Fastener Length: Between 0.517 inches and 0.547 inches **Head Style:** Oval/truss **Head Height:** Between 0.062 inches and 0.082 inches **Shank Diameter:** Between 0.186 inches and 0.190 inches **Shank Style:** Self-plugging **Head Major Diameter:** Between 0.600 inches and 0.650 inches **Expansion Device:** Plain stem-type t **Grip Length:** Between 0.250 inches and 0.375 inches **Shear Strength:** 425 single pounds per square inch Material: Aluminum alloy 5056 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:** Cadmium mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or phosphate zinc mandrel or zinc mandrel and chromate mandrel **Surface Treatment Specification:** Qq-p-416 federal specification all treatment responses mandrel or mil-p-16232 military specification 1st treatment response mandrel or qq-z-325, type 2, cl 3 federal specification 2nd treatment response mandrel Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: