

View Online at <https://aerobasegroup.com/nsn/5320-00-490-2242>

Fastener Length:

Between 0.487 inches and 0.517 inches

Head Style:

Universal

Head Height:

Between 0.041 inches and 0.061 inches

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.296 inches and 0.328 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.251 inches and 0.312 inches

Shear Strength:

590 single pounds per square inch

Material:

Aluminum alloy 5056

Material Specification:

Qq-a-430 federal specification single material response

Surface Treatment:

Cadmium mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or phosphate zinc mandrel or zinc mandrel and chromate mandrel

Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses mandrel or mil-p-16232 military specification 1st treatment response mandrel or qq-z-325, type 2, cl 3 federal specification 2nd treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.