## NSN 5320-00-490-2242

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-490-2242 Fastener Length: Between 0.487 inches and 0.517 inches **Head Style:** Universal **Head Height:** Between 0.041 inches and 0.061 inches **Shank Diameter:** Between 0.155 inches and 0.159 inches **Shank Style:** Self-plugging **Head Major Diameter:** Between 0.296 inches and 0.328 inches **Expansion Device:** Plain stem-type t **Grip Length:** Between 0.251 inches and 0.312 inches **Shear Strength:** 590 single pounds per square inch Material: Aluminum alloy 5056 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:** Cadmium mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or phosphate zinc mandrel or

Cadmium mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or phosphate zinc mandrel or zinc mandrel and chromate mandrel

## **Surface Treatment Specification:**

Qq-p-416 federal specification all treatment responses mandrel or mil-p-16232 military specification 1st treatment response mandrel or qq-z-325, type 2, cl 3 federal specification 2nd treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.