## NSN 5320-00-493-4103

Fiig: A040a0

Mil-std (military Standard):

Mil-a-8625 spec.



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-493-4103 **Fastener Length:** 0.414 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** 0.187 inches **Head Major Diameter:** 0.375 inches **Expansion Device:** Plain stem-type t **Grip Length:** Between 0.161 inches and 0.220 inches **Shear Strength:** 470 single pounds per square inch **Countersink Angle:** 120.0 degrees Material: Aluminum alloy 5056 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:** Cadmium stem or cadmium stem and chromate stem or cadmium stem and phosphate stem or phosphate zinc stem or phosphate zinc stem or zinc stem and chromate stem **Surface Treatment Specification:** Qq-p-416 federal specification 1st treatment response stem or mil-p-16232, ty z, cl2 military specification 2nd treatment response stem or mil-p-16232, ty z, cl 4b military specification 3rd treatment response stem or qq-z-325, type 2, cl 3 federal specification 4th treatment response stem Shelf Life: N/a **Unit Of Measure: Demilitarization:** No