

View Online at <https://aerobasegroup.com/nsn/5320-00-493-4104>

Fastener Length:

Between 0.529 inches and 0.650 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.185 inches and 0.190 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.310 inches and 0.385 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.251 inches and 0.375 inches

Shear Strength:

470 single pounds per square inch

Countersink Angle:

120.0 degrees

Material:

Steel comp 1006 stem or steel comp 1008 stem or steel comp 1009 stem or steel comp 1010 stem

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Zinc stem and chromate stem or cadmium stem or cadmium stem and chromate stem or cadmium stem and phosphate stem or phosphate zinc stem

Surface Treatment Specification:

Qq-z-325, type 2, cl 3 federal specification 1st treatment response stem or qq-p-416 federal specification 2nd treatment response stem or qq-p-416 federal specification 3rd treatment response stem or qq-p-416 federal specification 4th treatment response stem or mil-p-16232, ty z, cl2 military specification 5th treatment response stem or mil-p-16232, ty z, cl4 military specification 5th treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.