# NSN 5320-00-494-2311

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-494-2311

## Head Style:

Hexagon

**Head Height:** 

0.113 inches

## Shank Diameter:

Between 0.197 inches and 0.199 inches

## Shank Style:

Threaded self-plugging shank w/sleeve

## **Expansion Device:**

Serrated stem-type w

## Grip Length:

Between 1.095 inches and 1.156 inches

## Width Across Flats:

Between 0.305 inches and 0.312 inches

## Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

## Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

## Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn

standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

## Surface Treatment:

Cadmium sleeve and passivate sleeve

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

#### **Specification Data:**

80205-nas1669 professional/industrial association standard

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### **Demilitarization:**

No

## Fiig:

A040a0

## Mil-std (military Standard):

Mil-s-5626 spec.