

View Online at <https://aerobasegroup.com/nsn/5320-00-494-7991>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.7600 inches and 0.7800 inches

Head Style:

Err-090

Head Height:

Between 0.0590 inches and 0.0690 inches

Width Between Flats:

Between 0.09470 inches and 0.09670 inches

Shank Diameter:

Between 0.2797 inches and 0.2807 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.3870 inches and 0.4120 inches

Grip Length:

Between 0.3700 inches and 0.3800 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.2500 inches

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp e4340

Material Specification:

Mil-s-6758 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-5000 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.