

View Online at <https://aerobasegroup.com/nsn/5320-00-494-7991>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.7600 inches and 0.7800 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.0590 inches and 0.0690 inches

**Width Between Flats:**

Between 0.09470 inches and 0.09670 inches

**Shank Diameter:**

Between 0.2797 inches and 0.2807 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.3870 inches and 0.4120 inches

**Grip Length:**

Between 0.3700 inches and 0.3800 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.2500 inches

**Material:**

Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp e4340

**Material Specification:**

Mil-s-6758 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-5000 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6758 spec.