

View Online at <https://aerobasegroup.com/nsn/5320-00-498-0826>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.845 inches and 0.865 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-rivet, multiple grooved

Head Major Diameter:

Between 0.297 inches and 0.302 inches

Grip Length:

Between 0.406 inches and 0.500 inches

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Break stem type

Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.