

View Online at <https://aerobasegroup.com/nsn/5320-00-498-7251>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.565 inches and 0.585 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.297 inches and 0.302 inches

End Application:

4w/s: aircraft (ac-130h, mc-130h, ec-130e, hc-130); aircraft, hornet f/a-18; aircraft, orion p-3; deep submergence systems programs (dssp); aircraft, phantom f-4; aircraft, galaxy c-5; aircraft, b-1b; aircraft, eagle f-15; aircraft, harrier av-8b

Grip Length:

0.255 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Countersink Angle:

100.0 degrees

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0