
## NSN 5320-00-500-5067

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.347 inches and 1.367 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.078 inches and 0.088 inches

#### Width Between Flats:

Between 0.158 inches and 0.162 inches

#### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.822 inches

Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

220000 pounds per square inch

#### **Thread Size:**

0.375 inches

## Shear Strength:

132000 single pounds per square inch

#### Material:

Steel comp h11

## Material Specification:

Ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

## Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

# NSN 5320-00-500-5067

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

