

View Online at <https://aerobasegroup.com/nsn/5320-00-502-1012>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.050 inches and 2.070 inches

Head Style:

Flat countersunk undercut

Head Height:

Between 0.1571 inches and 0.1601 inches

Width Between Flats:

Between 0.2207 inches and 0.2242 inches

Shank Diameter:

Between 0.4985 inches and 0.4995 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 1.0068 inches and 1.0139 inches

Lubrication:

Cetyl alcohol

Grip Length:

1.385 inches

Thread Qty Per Inch (tpi):

20

Thread Size:

0.500 inches

Shear Strength:

132000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Furnished with synthetic rubber o-ring

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0