NSN 5320-00-502-1017

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-502-1017 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.113 inches and 2.133 inches **Head Style:** Flat countersunk undercut **Head Height:** Between 0.1571 inches and 0.1601 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.4985 inches and 0.4995 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 1.0068 inches and 1.0139 inches Lubrication: Cetyl alcohol **Grip Length:** 1.448 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Shear Strength:** 132000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Cetyl alcohol lubrication, furnished with synthetic rubber o-ring Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:**

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Nickel and cadmium

Unjf

NSN 5320-00-502-1017

Pin-rivet - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0