

NSN 5320-00-502-1021 Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-502-1021 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.363 inches and 2.383 inches **Head Style:** Flat countersunk undercut **Head Height:** Between 0.1571 inches and 0.1601 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.4985 inches and 0.4995 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 1.0068 inches and 1.0139 inches **Grip Length:** 1.698 inches **Features Provided:** Washer Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Shear Strength:** 132000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-00-502-1021

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0