NSN 5320-00-502-1048

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-502-1048 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.990 inches and 1.010 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.127 inches and 0.130 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol **Grip Length:** 0.510 inches Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 20200 double pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:**

Unjf
Shelf Life:
N/a
Unit Of Measure:

NSN 5320-00-502-1048

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0