NSN 5320-00-502-1089

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-502-1089



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.250 inches and 2.270 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.190 inches and 0.193 inches

Shank Diameter:

Between 0.4360 inches and 0.4370 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.662 inches and 0.668 inches

Lubrication:

Cetyl alcohol

Grip Length:

1.635 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Thread Size:

0.438 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-00-502-1089

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

