NSN 5320-00-502-1821

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-502-1821 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.240 inches and 1.260 inches **Head Style:** Flat countersunk undercut **Head Height:** Between 0.0870 inches and 0.0898 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.6287 inches and 0.6335 inches **Grip Length:** 0.760 inches **Features Provided:** Washer Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5320-00-502-1821

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0