

View Online at <https://aerobasegroup.com/nsn/5320-00-503-7274>

**Fastener Length:**

0.469 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.200 inches and 0.204 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.349 inches and 0.357 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.188 inches and 0.250 inches

**Shear Strength:**

1200 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Nickel alloy 400 locking ring or nickel alloy r-405 locking ring

**Material Specification:**

Qq-n-281 federal specification all material responses locking ring

**Surface Treatment:**

Anodize body or chromate body

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response body or mil-s-5541 military specification 2nd treatment response body

**Specification Data:**

80205-nas1739 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.