## NSN 5320-00-505-6507

View Online at https://aerobasegroup.com/nsn/5320-00-505-6507

Pin-rivet - Page 1 of 2



**Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.677 inches and 0.697 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.064 inches and 0.065 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.256 inches and 0.261 inches Lubrication: Cetyl alcohol **Grip Length:** 0.385 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 132000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjc Shelf Life: N/a

## NSN 5320-00-505-6507

Pin-rivet - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A528u0