NSN 5320-00-505-7308

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-505-7308 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.928 inches and 0.948 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.127 inches and 0.130 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol **Grip Length:** 0.448 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 20200 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-00-505-7308

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0