NSN 5320-00-505-7310

View Online at https://aerobasegroup.com/nsn/5320-00-505-7310

Pin-rivet - Page 1 of 2



Thread Class: За **Thread Direction:** Right-hand Fastener Length: Between 0.627 inches and 0.647 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.377 inches and 0.381 inches Lubrication: Cetyl alcohol **Grip Length:** 0.322 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 7480 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-00-505-7310

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0