## NSN 5320-00-508-8381

View Online at https://aerobasegroup.com/nsn/5320-00-508-8381

Pin-rivet - Page 1 of 2



**Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.552 inches and 0.572 inches **Head Style:** Err-090 **Head Height:** Between 0.055 inches and 0.060 inches Width Between Flats: Between 0.064 inches and 0.065 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style: Head Major Diameter:** Between 0.306 inches and 0.322 inches Lubrication: Cetyl alcohol **Grip Length:** 0.260 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 5570 double pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjc Shelf Life: N/a

## NSN 5320-00-508-8381

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0