NSN 5320-00-508-8385

Pin-rivet - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5320-00-508-8385

Right-hand Fastener Length: Between 0.864 inches and 0.884 inches Head Style: Err-090 Head Height: Between 0.055 inches and 0.065 inches					
Between 0.864 inches and 0.884 inches Head Style: Err-090 Head Height:					
Head Style: Err-090 Head Height:					
Err-090 Head Height:					
Head Height:					
_					
Between 0.055 inches and 0.065 inches					
Width Between Flats:					
Between 0.064 inches and 0.065 inches					
Shank Diameter:					
Between 0.1625 inches and 0.1635 inches					
Shank Style:					
Pin-rivet, straight, threaded					
Head Major Diameter:					
Between 0.306 inches and 0.322 inches					
Lubrication:					
Cetyl alcohol					
Grip Length:					
0.572 inches					
Thready Qty Per Inch (tpi):					
32					
Min. Tensile Strength (psi):					
220000 pounds per square inch					
Thread Size:					
Thread Size: 0.164 inches					
0.164 inches					
0.164 inches Shear Strength:					
0.164 inches Shear Strength: 5570 double pounds per square inch					
0.164 inches Shear Strength: 5570 double pounds per square inch Material:					
0.164 inches Shear Strength: 5570 double pounds per square inch Material: Steel comp h11					
0.164 inches Shear Strength: 5570 double pounds per square inch Material: Steel comp h11 Material Specification:					
0.164 inches Shear Strength: 5570 double pounds per square inch Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response					
0.164 inches Shear Strength: 5570 double pounds per square inch Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment:					
0.164 inches Shear Strength: 5570 double pounds per square inch Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Nickel and cadmium					
0.164 inches Shear Strength: 5570 double pounds per square inch Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Nickel and cadmium Surface Treatment Specification:					
0.164 inches Shear Strength: 5570 double pounds per square inch Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Nickel and cadmium Surface Treatment Specification: Ams 2416 assn standard all treatment responses					
0.164 inches Shear Strength: 5570 double pounds per square inch Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Nickel and cadmium Surface Treatment Specification: Ams 2416 assn standard all treatment responses Thread Series Designator:					

NSN 5320-00-508-8385

Pin-rivet - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0