NSN 5320-00-508-8425

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-508-8425 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.003 inches and 1.023 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.349 inches and 0.354 inches Lubrication: Cetyl alcohol **Grip Length:** 0.693 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 2540 double pounds per square inch **Countersink Angle:** 100.0 degrees **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-430 military specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-00-508-8425

Pin-rivet - Page 2 of 2



Demilitarization:	
No	
Fiig:	
A528u0	

Unit Of Measure:

Mil-std (military Standard):

spec.