# NSN 5320-00-508-8683

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.697 inches and 0.717 inches

# Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

# Width Between Flats:

Between 0.0947 inches and 0.0967 inches

### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.387 inches and 0.412 inches

# Lubrication:

Cetyl alcohol

# Grip Length:

0.317 inches

# Thready Qty Per Inch (tpi):

28

# Thread Size:

0.250 inches

# Shear Strength:

4500 double pounds per square inch

# Heat Treatment:

T-6 solution heat treated

# Material:

Aluminum alloy 7075

# Material Specification:

Qq-a-430 federal specification single material response or qq-a-225/9 federal specification single material response

# Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

# NSN 5320-00-508-8683

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.

