## NSN 5320-00-508-8690

View Online at https://aerobasegroup.com/nsn/5320-00-508-8690

Pin-rivet - Page 1 of 2



**Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.223 inches and 1.243 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5554 inches and 0.5604 inches Lubrication: Cetyl alcohol **Grip Length:** 0.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 132000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5320-00-508-8690

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0