
# NSN 5320-00-508-8754

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.832 inches and 0.843 inches

# Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

0.448 inches

# Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

220000 pounds per square inch

#### Thread Size:

0.250 inches

#### Shear Strength:

132000 single pounds per square inch

#### Material:

Nickel alloy 718

#### Material Specification:

Ams 5662 assn standard single material response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-00-508-8754

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

