# NSN 5320-00-508-8759

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-508-8759



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.947 inches and 0.967 inches

#### Head Style:

Err-090

### Head Height:

Between 0.059 inches and 0.069 inches

### Width Between Flats:

Between 0.0947 inches and 0.3495 inches

### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

Lubrication:

Cetyl alcohol

## Grip Length:

0.572 inches

## Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

220000 pounds per square inch

## Thread Size:

0.250 inches

# Shear Strength:

132000 single pounds per square inch

## Material:

Nickel alloy 718

# Material Specification:

Ams 5662 assn standard single material response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-00-508-8759

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

