# NSN 5320-00-508-8770

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-508-8770



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.010 inches and 1.030 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

### Width Between Flats:

Between 0.095 inches and 0.097 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.415 inches and 0.440 inches

## Lubrication:

Cetyl alcohol

# Grip Length:

0.635 inches

# Thready Qty Per Inch (tpi):

28

### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.250 inches

### Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy

### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-00-508-8770

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

