# NSN 5320-00-508-8818

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-508-8818

# Fastener Length:

0.638 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.155 inches and 0.159 inches

## Head Major Diameter:

Between 0.282 inches and 0.290 inches

## **Expansion Device:**

Serrated stem-type w

## Grip Length:

Between 0.438 inches and 0.500 inches

# Shear Strength:

1090 single pounds per square inch

## **Countersink Angle:**

Between 98.5 degrees and 101.5 degrees

# Material:

Nickel alloy 400 locking ring or nickel alloy r-405 locking ring

# Material Specification:

Qq-n-281, alloy 400, class a federal specification 1st material response locking ring or qq-n-281, alloy r-405, class b federal specification 2nd

material response locking ring

## Surface Treatment:

Silver stem

## Surface Treatment Specification:

Qq-s-365, type 2 federal specification single treatment response stem

## **Specification Data:**

80205-nas1399 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# Fiig:

A040a0