

View Online at <https://aerobasegroup.com/nsn/5320-00-510-7822>

**Fastener Length:**

Between 0.428 inches and 0.468 inches

**Head Style:**

Universal

**Head Height:**

Between 0.054 inches and 0.064 inches

**Shank Diameter:**

Between 0.123 inches and 0.127 inches

**Shank Style:**

Drive pin

**Head Major Diameter:**

Between 0.238 inches and 0.262 inches

**Expansion Device:**

Drive stem-type h

**Grip Length:**

0.359 inches

**Heat Treatment:**

T-4 solution heat treated

**Material:**

Steel comp 301 stem or steel comp 302 stem or steel comp 303 stem or steel comp 303f stem or steel comp 303s stem or steel comp 303se stem or steel comp 304 stem or steel comp 304l stem or steel comp 305 stem or steel comp 308 stem or steel comp 309 stem or steel comp 309s stem or steel comp 310 stem or steel comp 310s stem or steel comp 314 stem or steel comp 316 stem or steel comp 316l stem or steel comp 317 stem or steel comp 321 stem or steel comp 323 stem or steel comp 324 stem or steel comp 347 stem or steel comp 348 stem or steel comp 385 stem

**Material Specification:**

Qq-a-430 federal specification single material response body

**Surface Treatment:**

Passivate stem

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.