

View Online at <https://aerobasegroup.com/nsn/5320-00-526-2806>

**Fastener Length:**

0.198 inches

**Head Style:**

Universal

**Head Height:**

Between 0.054 inches and 0.064 inches

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.238 inches and 0.262 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.025 inches and 0.062 inches

**Shear Strength:**

238 single pounds per square inch

**Heat Treatment:**

H-38 strain hardened locking ring

**Material:**

Aluminum alloy 5056 locking ring

**Material Specification:**

Qq-a-430 federal specification single material response locking ring

**Surface Treatment:**

Anodize stem or chromate stem

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

**Specification Data:**

80205-nas1398 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.