NSN 5320-00-527-1184

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-527-1184

| view Online at https://derobasegroup.com/nsn/3320-00-327-1104 |
|--|
| Fastener Length: |
| Between 1.179 inches and 1.209 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.258 inches and 0.260 inches |
| Shank Style: |
| Threaded self-plugging shank w/sleeve |
| Head Major Diameter: |
| 0.463 inches |
| Expansion Device: |
| Threaded stem |
| Grip Length: |
| Between 0.396 inches and 0.436 inches |
| Hardness Rating: |
| 30.0 rockwell c and 45.0 rockwell c |
| Shear Strength: |
| 7200 double pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel |
| Material Specification: |
| Ams 5735 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Specification Data: |
| 80205-nas1672 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |