

View Online at <https://aerobasegroup.com/nsn/5320-00-530-0606>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.665 inches

**Head Style:**

Flush countersunk

**Head Height:**

0.104 inches

**Width Between Flats:**

0.094 inches

**Shank Diameter:**

Between 0.2630 inches and 0.2650 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.507 inches

**Grip Length:**

Between 0.563 inches and 0.625 inches

**Thready Qty Per Inch (tpi):**

48

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.216 inches

**Countersink Angle:**

100.0 degrees

**Special Features:**

Hex socket in head

**Material:**

Steel comp 8740 or aluminum alloy

**Material Specification:**

66 federal standard 1st material response or specification 713 huck mfg co mfr ref 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0