NSN 5320-00-530-0607

Pin-rivet - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5320-00-530-0607 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.732 inches **Head Style:** Flush countersunk **Head Height:** 0.104 inches Width Between Flats: 0.094 inches **Shank Diameter:** Between 0.2630 inches and 0.2650 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.507 inches **Grip Length:** Between 0.626 inches and 0.688 inches Thready Qty Per Inch (tpi): 48 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.216 inches **Countersink Angle:** 100.0 degrees **Special Features:** Hex socket in head Material: Steel comp 8740 **Material Specification:** Fed standard 66 federal standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Uns Shelf Life:

NSN 5320-00-530-0607

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0