

View Online at <https://aerobasegroup.com/nsn/5320-00-530-6133>

Fastener Length:

Between 0.229 inches and 0.249 inches

Head Style:

Err-090

Head Height:

Between 0.037 inches and 0.047 inches

Shank Diameter:

Between 0.1535 inches and 0.1560 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.242 inches and 0.262 inches

Grip Length:

Between 0.062 inches and 0.125 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 8740 or steel comp 8740 or steel comp 6150 or steel comp 4340 or steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 4130 or steel comp 4037 or steel comp 3135 or steel comp 8735

Material Specification:

Mil-s-6049 military specification 1st material response or ams 6322 assn standard 2nd material response or mil-s-8503 military specification 3rd material response or ams 6415 assn standard 4th material response or mil-s-5000 military specification 5th material response or mil-s-5000 military specification all material responses or mil-s-5626 military specification 6th material response or mil-s-6758 military specification 7th material response or mil-s-8695 cond c4 military specification 8th material response or ams 6330 assn standard 9th material response or mil-s-6098 military specification 10th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Specification Data:

80205-nas1054 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.